



THE FLEXIBLE NETWORK PRINTER.

With an excellent 40 pages per minute print speed, an integrated network interface and double-sided printing as standard, the FS-3920DN is a superb workgroup device. It has an outstanding array of features and paper-handling options to accommodate different user needs. Furthermore, this dependable partner knows how to impress with comprehensive security features and an exceptionally low cost per page.

- ▶ Up to 40 pages per minute in A4 with 1,200 dpi resolution
- ▶ Duplex as standard for double-sided printing
- ▶ Up to 5 paper trays for superior flexibility and high capacity
- ▶ A6 printing from internal paper cassette
- ▶ Powerful controller with 128 MB RAM as standard
- ▶ USB, parallel and network connectivity as standard
- ▶ Direct PDF Print from USB Flash memory device
- ▶ Exceptionally low printing costs in its class



FS-3920DN

MONOCHROME WORKGROUP PRINTER FOR A4 FORMATS

ECOSYS With their long-life components, ECOSYS devices are designed to maximise durability and minimise both direct costs such as consumables, and indirect costs such as maintenance and administration. The cartridge-free system requires that only the toner has to be replaced regularly. The modular design concept allows you to add productivity-enhancing options and a wide-variety of paper-handling capabilities as required. Integrated system software provides long-term cross-network compatibility. Kyocera's long-life components cost you and the environment less.

PRESCRIBE IIe

With the KYOCERA page design and control language PRESCRIBE IIe, even complex graphics, logos and forms (including multipart forms) can be created on any system and stored in the printer. They can be recalled from the printer's memory as needed, reducing network congestion.

The KM NetViewer

The KM NetViewer enables complete monitoring and control of all ECOSYS printers and KYOCERA multifunction copiers from any Windows® PC. It provides ideal network administration using the industry-standard SNMP protocol.

Status Monitor and Command Center

The Status Monitor visually portrays the printer's condition and gives direct access to the Command Center for the modification of advanced settings not available in the standard driver (e.g. IP settings, sleep mode or disabling the control panel).

USB Host Interface for USB Flash Memory

PDF files can be printed directly from a USB Flash Memory device (e.g. USB stick) via the USB host interface. Documents are selected directly using the printer's control panel. No computer is required.

General

Technology

KYOCERA ECOSYS Laser

Engine speed

Up to 40 pages per minute in A4

Resolution

1,200 dpi

Duty cycle

Max. 200,000 pages per month

Max. average 25,000 pages per month
(average 8000 pages per month)

Warm-up time

Approx. 17 seconds or less from power on

Time to first page

Approx. 10.5 seconds or less

Dimensions (W x D x H)

382 mm x 394 mm x 320 mm

Weight

Approx. 16.7 kg (main unit)

Power source

220/240 V, 50/60 Hz

Power consumption

Printing: 641 W

Stand-by: 9.5 W

Power-Saving (ECOpower): 5.9 W

Noise (ISO 7779 / ISO 9296)

Printing: 54 dB(A)

Stand-by: 30 dB(A)

Safety standards

TÜV/GS, CE, PTS

This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

Paper Handling

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity

100-sheet multi-purpose tray; 60–220 g/m²;

A4, A5, A6, B5, Letter, Legal, Custom

(70 x 148 – 216 x 356 mm)

500-sheet universal paper cassette, 60–120 g/m²;

A4, A5, A6, B5, Letter, Legal, Custom

(140 x 210 mm – 216 x 356 mm)

Max. input capacity incl. options: 2,500 sheets

Duplex unit

Duplex as standard supports A4, A5, B5, Letter, Legal, Custom (140 x 210 mm – 216 x 356 mm), 60–120 g/m²

Output capacity

500-sheet-face-down with paper full sensor and optional

250-sheet-face-up with PT-310

Controller

CPU

PowerPC 440/600 MHz

Memory

128 MB RAM, can be increased to 1,152 MB RAM as an option

Standard interface

High-speed bi-directional parallel (IEEE 1284), USB 2.0 (Hi-Speed), USB Host Interface dedicated for USB Flash Memory device, Fast Ethernet 10Base-T/100Base-TX, Slot for optional internal print server or hard disc, Slot for optional CompactFlash*-Card

Controller language

Prescribe IIe

Emulations

PCL6/PCL5c incl. P.J.L, KPDL 3 (PostScript 3 compatible), PDF Direct Print, Line Printer, IBM Proprinter X24E, Epson LQ-850, Diablo 630

Operating systems

All current Windows operating systems, Mac OS X Version 10.2 or higher, UNIX, LINUX as well as other operating systems on request

Fonts/Barcodes

93 scalable fonts for PCL/PostScript*, 8 fonts for Windows Vista*, 1 Bitmap font, 45 barcodes (e.g. EAN8, EAN13, EAN128) with automatic generation of checksums as well as support of two-dimensional barcodes PDF-417 under PRESCRIBE (PCL and other barcodes available as an option)

Integrated Accounting

100 department codes

Consumables

TK-350 Toner-Kit

Microfine toner for 15,000 A4 pages in accordance with ISO/IEC 19752

Capacity of starter toner is 7,500 A4 pages in accordance with ISO/IEC 19752

Options

PF-310 Paper feeder (max. 3 units)

Max. 500 sheets; 60–120 g/m²; A4, A5, B5, Letter, Legal, Custom (148 x 210 mm – 216 x 356 mm)

PF-315 Bulk paper feeder and PB-315 Printer base

Max. 2,000 sheet, 60–200 g/m², not to be combined with PF-310 or EF-310

HS-315 Offline bulk stacker

Max. 2,000 sheet face-up, 60–200 g/m²

HS-315A for combination with optional

PF-315 bulk paper feeder

HS-315B for combination with 3 optional paper feeders PF-310

EF-310 Envelope feeder

For max. 70 normal envelopes or max. 100 air mail envelopes up to A6 size

PT-310 Paper tray

250-sheet-face-up output tray

Memory upgrade

MDDR2-128: 128 MB; MDDR2-256: 256 MB;

MDDR2-512: 512 MB, MDDR2-1024: 1.024 MB

CompactFlash*-Card

1 slot (up to 4 GB) for printing forms, fonts, logos, macro storage

USB Flash Memory

Supports PDF direct printing via USB Host Interface

HD-5a Hard disk

40 GB for easy document management

Optional interface

PS1109 Gigabit Ethernet:

10BaseT / 100BaseTX / 1000BaseT (RJ-45)

Warranty

1-year warranty as standard. KYOCERA guarantees the drum and developer for 3 years or maximum 300,000 pages (whichever occurs sooner), provided the printer is used and cleaned in accordance with the service instructions.

KYO LIFE



Your KYOCERA Business Partner:



Product depicted includes optional extras.

*KYOCERA does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks and their respective holders and are hereby acknowledged.

 **KYOCERA**